1	What is claimed is:				
2	1. A method of managing tool execution via roles on a computer system while				
3	maintaining computer system security, wherein the computer system comprises a				
4	plurality of roles, comprising:				
5	delegating one or more tools to a user based on a first role, wherein a				
6	tool provides root access and the first role enables the user to run the				
7	delegated tool(s);				
8	identifying one of the plurality of roles to be disabled, wherein the				
9	role identified to be disabled is the first role;				
10	accessing the role identified to be disabled so that the status of the				
11	role identified to be disabled may be changed; and,				
12	disabling the role identified to be disabled, whereby the status of the				
13	role identified to be disabled is changed, so that the user cannot run the				
14	delegated tool(s).				
15					
16	2. The method of claim 1, wherein the first role is represented by a role object				
17	comprising an enablement attribute that has a value that determines whether the first				
18	role is enabled or disabled, wherein disabling the role identified to be disabled				
19	comprises:				
20	setting the enablement attribute value so that the first role is disabled.				
21					
22	3. The method of claim 2, wherein the user is represented by a user object,				
23	wherein delegating one or more tools to a user based on a role comprises linking the				
24	role object to the user object with an authorization object.				
25					
26	4. The method of claim 2, wherein identifying one of the plurality of roles to				
27	be disabled comprises a root user entering, through a command line interface				
28	("CLI") or graphic user interface ("GUI"), a command that identifies the role object.				
29					
30	5. The method of claim 4, wherein the CLI or GUI operate in a process space				
31	and wherein accessing the role identified to be disabled comprises returning the role				
32	object to the CLI or GUI process space.				

1	6. The method of claim 1, wherein delegating one or more tools to a user base
2	on a role comprises:
3	a) authorizing the first role for the user, the first role comprising
4	the delegated tool(s); and
5	b) authorizing a machine of the computer system for the first
6	role, wherein the computer system comprises a plurality of machines and the
7	user is enabled to utilize the first role only on authorized machines, whereb
8	utilizing the first role comprises running the one or more tools of the first
9	role.
10	
11	7. The method of claim 1, further comprising:
12	identifying one of the plurality of roles to be enabled, wherein the
13	role identified to be enabled is the first role;
14	accessing the role identified to be enabled; and
15	enabling the role identified to be enabled, whereby the status of the
16	role identified to be enabled is changed, so that the user can run the
17	delegated tool(s).
18	
19	8. A computer readable medium comprising instructions for managing tool
20	execution via roles on a computer system while maintaining computer system
21	security, wherein the computer system comprises a plurality of roles, by:
22	delegating one or more tools to a user based on a first role, wherein a
23	tool provides root access and the first role enables the user to run the
24	delegated tool(s);
25	identifying one of the plurality of roles to be disabled, wherein the
26	role identified to be disabled is the first role;
27	accessing the role identified to be disabled so that the status of the
28	role identified to be disabled may be changed; and,
29	disabling the role identified to be disabled, whereby the status of the
30	role identified to be disabled is changed, so that the user cannot run the
31	delegated tool(s).
32	

1	9. The computer readable medium of claim 8, wherein the authorized role is				
2	represented by a role object comprising an enablement attribute that has a value that				
3	determines whether the first role is enabled or disabled, wherein disabling the role				
4	identified to be disabled comprises:				
5	setting the enablement attribute value so that first role is disabled.				
6					
7	10. The computer readable medium of claim 9, wherein the user is represented				
8	by a user object, wherein delegating one or more tools to a user based on a role				
9	comprises linking the role object to the user object with an authorization object.				
10					
11	11. The computer readable medium of claim 9, wherein identifying one of the				
12	plurality of roles to be disabled comprises a root user entering, through a CLI or				
13	GUI, a command that identifies the role object.				
14					
15	12. The computer readable medium of claim 11, wherein the CLI or GUI				
16	operate in a process space and wherein accessing the role identified to be disabled				
17	comprises returning the role object to the CLI or GUI process space.				
18					
19	13. The computer readable medium of claim 8, wherein delegating one or more				
20	tools to a user based on a role comprises:				
21	a) authorizing the first role for the user, the authorized role				
22	comprising the delegated tool(s); and				
23	b) authorizing a machine of the computer system for the first				
24	role, wherein the computer system comprises a plurality of machines and the				
25	user is enabled to utilize the first role only on authorized machines, whereby				
26	utilizing the first role comprises running the one or more tools of the first				
27	role.				
28					

1	14.	The computer readable medium of claim 8, further comprising instructions
2	for ma	inaging tool execution via roles on the computer system, by:
3		identifying one of the plurality of roles to be enabled, wherein the
4		role identified to be enabled is the first role;
5		accessing the role identified to be enabled; and
6		enabling the role identified to be enabled, whereby the status of the
7		role identified to be enabled is changed, so that the user can run the
8		delegated tool(s).
9		
10	15.	A method of managing tool execution via roles on a computer system while
11	mainta	ining computer system security, wherein the computer system comprises a
12		ty of roles, comprising:
13		identifying one of the plurality of roles to be enabled, wherein the
14		role identified to be enabled is a first role of a user, wherein the first role
15		enables the user to run one or more delegated tools, wherein a tool provides
16		root access for performing a specific task in the computer system;
17		accessing the role identified to be enabled so that the status of the
18		role identified to be enabled may be changed; and,
19		enabling the role identified to be enabled, whereby the status of the
20		role identified to be enabled is changed, so that the user can run the
21		delegated tool(s).
22		
23	16.	The method of claim 15, further comprising:
24		identifying one of the plurality of roles to be disabled, wherein the
25		role identified to be disabled is the first role;
26		accessing the role identified to be disabled; and
27		disabling the role identified to be disabled, whereby the status of the
28]	role identified to be disabled is changed, so that the user cannot run the
29	•	delegated tool(s).
30		
31	17.	The method of claim 16, wherein the user runs at least one of the delegated
32	tool(s) a	after the enabling step is performed, wherein identifying one of the plurality
33	of roles	to be disabled comprises a root user determining that the user is finished
34	running	the delegated tool(s).

21

1			
2	18. The method of claim 15, wherein the user is a customer engineer, wherein		
3	identifying one of the plurality of roles to be enabled comprises a root user		
4	determining that the customer engineer needs to run at least one of the delegated		
5	tool(s).		
6			
7	19. The method of claim 15, wherein the first role is represented by a role object		
8	comprising an enablement attribute that has a value that determines whether the first		
9	role is enabled or disabled, wherein enabling the role identified to be enabled		
10	comprises:		
11	setting the enablement attribute value so that the first role is enabled.		
12			
13	20. The method of claim 19, wherein the enablement attribute value is a		
14	Boolean value and setting the enablement attribute value comprises setting the		
15	enablement attribute value to true.		